

SPICER®



Spicer® XFE 75W-90 Extra Fuel-Efficient Synthetic Gear Lubricant



2.5% Fuel Savings. Unparalleled performance.

Our most fuel-efficient gear lubricant to date, Spicer® XFE 75W-90 delivers fuel savings that will make a noticeable impact on your bottom line. Engineered to meet the specifications of linehaul, vocational heavy-duty axles, and light-duty axles. You will still experience longer gear life and better operating performance, even in extreme temperatures. You can enjoy a 2.5% fuel savings improvement over standard 75W-90 oil, and extend the warranty on your Spicer heavy-duty or medium-duty carriers (see back for more details).



Spicer® XFE 75W-90 Extra Fuel-Efficient Synthetic Gear Lubricant



Advantages and Benefits:

- Quantifiable **2.5%** fuel savings improvement over 75W-90 oil* – calculate the savings at SpicerParts.com/FuelSavings
- Reduced gear wear
- Reduced maintenance
- Less oil disposal
- Decreased vehicle downtime
- Excellent seal compatibility
- Maximum extreme hot and cold temperature performance
- Extended drain interval up to 500,000 miles
- Extended warranty protection

Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant is approved to meet the most stringent industry specifications, as established by Dana:

- Dana SHAES 256 Rev C
- Dana SHAES 429
- SAE J2360; API MT-1 and API GL-5
- Meritor O76-N
- Mack Truck Go-J Plus
- Navistar MPAPS B6821

Get an Extended Warranty When You Purchase Spicer® Gear Lube!

Purchase a new heavy-duty or medium-duty Spicer service carrier for your linehaul vehicle and fill it with Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant. When doing so, you can extend your 2-year unlimited warranty by an additional 12 months for a total of **3 years**. For more details on how to register for this extended warranty, visit our website at SpicerParts.com/Carriers.

Characteristics:

Properties	Unit	Typical Value	Method
SAE class	75W-90	SAE J 306	
Density at 15.6 °C	lbs/gal	0.864 (7.21)	ASTM D 1298
Viscosity index	–	169	ASTM D 2270
at 100° C	mm ² /s	15.2	ASTM D 445
at 40° C	mm ² /s	95.4	ASTM D 445
at -40° C	mPas	45, 100	ASTM D 2983
Flash Point	°C	210	ASTM D 92
Pour Point	°C	-57	ASTM D 97

NOTE: Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally.

Size	Part #
5-gallon pail	XFE75W90-P

Calculate the savings at SpicerParts.com/FuelSavings.

To learn more about Spicer® XFE 75W-90 extra fuel-efficient synthetic gear lubricant and other genuine Spicer products, visit SpicerParts.com today!

* Fuel savings based on initial results of applications tested. Results may vary.

Please refer to material safety data sheet for handling details. Subject to appropriate storage in closed original containers under the usual storage and temperature conditions. Spicer XFE 75W-90 extra fuel-efficient synthetic gear lubricant is stable for at least 3 years.

SpicerParts.com/Lubricants

Dana Aftermarket Group

PO Box 1000 Maumee, Ohio 43537

Warehouse Distributors: 1.800.621.8084

OE Dealers: 1.877.777.5360

Follow SpicerParts [f](#) [t](#) [@](#) [v](#) [in](#)

© 2019 Dana Limited. All rights reserved. Sprinter is a registered trademark of Mercedes-Benz. SPR-XFE-SS-62019

SPICER®

